

# **SURPLUSTRADERS.NET**

PO Box 276  
Alburg, VT 05440

Website: [www.surplustraders.net](http://www.surplustraders.net)  
Email: [sales@surplustraders.net](mailto:sales@surplustraders.net)

Tel: 800-341-6468  
Fax: 888-661-3032

This spec sheet is provided courtesy of Surplustraders.net

If you are looking for brand names, model numbers or other products that are not currently represented in this spec sheet, please, give us a call or send us an email with your requirements so we can further discuss your needs.

Thank you

Ph: 866-831-8848

Fax: 888-661-3032

Email: [sales@surplustraders.net](mailto:sales@surplustraders.net)

Website: [www.surplustraders.net](http://www.surplustraders.net)

TSS-2009M HP Debrand 2009m

LCD feature	Specification
Display size	20-inch (50.8 cm) diagonal and viewable image
Display type	Thin-Film Transistor LCD active matrix BriteView technology
Input terminal	VGA 15-pin D-type connector DVI-D connector
Scanning frequency	Horizontal scan range 24-82 KHz Vertical scan range 50-76 Hz
Recommended resolution (H x V)	1680 x 1050 @ 60 Hz
Contrast ratio	up to 1000:1
Response time	5 ms (on-off)
Pixel pitch	0.258 mm
Power source - AC/DC adapter	Input rating: 100 to 240V~ Power consumption: <52 W in operating mode, <2 W in sleep mode
Operating environment	Temperature: 32 degrees F to 104 degrees F (0 degrees C to 40 degrees C) Humidity: 15% RH through 90% RH (non-condensing)
Storage environment	Temperature: -4 degrees F to 140 degrees F (-20 degrees C to 60 degrees C) Humidity: 15% RH through 90% RH (non-condensing)
Dimensions	H x W x D, including base: 15.6 x 19.2 x 7.2 inches (39.6 x 48.7 x 18.2 cm)
Weight	Unpacked: 13.3 lbs (6 Kg)
EMI standard	FCC Class B
Mounting	Standard VESA 4-hole 100 mm x 100 mm
EPA Energy Star	As an Energy Star Partner, Hewlett-Packard has determined that this product meets the Energy Star guidelines for energy efficiency.