

# **SURPLUSTRADERS.NET**

PO Box 276  
Alburt, VT 05440

Website: [www.surplustraders.net](http://www.surplustraders.net)  
Email: [marshall@surplustraders.net](mailto:marshall@surplustraders.net)

Tel: 514-739-2950  
Fax: 514-345-8303

This spec sheet is provided courtesy of Surplustraders.net

If you are looking for brand names, model numbers or other products that are not currently represented in this spec sheet, please, give me a call or send me an email with your requirements so we can further discuss your needs.

Thank you

Marshall Duskes

Ph: 514-739-2950

Fx: 514-345-8303

Email: [marshall@surplustraders.net](mailto:marshall@surplustraders.net)

Website: [www.surplustraders.net](http://www.surplustraders.net)

**Specs:**

Model 1547L

Availability Worldwide

Case/bezel color Black

Display Size: 15" diagonal

Aspect ratio: 4:3

Useful screen area Horizontal: 11.9" (304 mm)

Vertical: 8.9" (228 mm)

Monitor dimensions

(dimensions shown are with horizontal mounting bracket) Projected Capacitive/ThruTouch width: 18.1" (460 mm)

Projected Capacitive/ThruTouch height: 11.5" (293 mm)

Projected Capacitive/ThruTouch depth: 2.52" (64 mm)

Other monitors width: 18.1" (460 mm)

Other monitors height: 11.6" (296 mm)

Other monitors depth: 2.83" (72 mm)

Native (optimal) resolution 1024 x 768 at 60, 70 or 75 Hz

Other supported resolutions 1024 x 768 at 65 Hz (Sun)

832 x 624 at 75 Hz (Mac)

800 x 600 at 56, 60, 72 or 75 Hz

720 x 400 at 70 Hz

720 x 350 at 70 Hz; 640 x 480 at 60, 66 (Mac), 72 or 75 Hz

Colors 16.2 million with dithering (8 bit)

Brightness LCD panel: 350 nits (typical)

with AccuTouch: 287 nits (typical)

with CarrollTouch: 322 nits (typical)

with IntelliTouch: 322 nits (typical)

with projected capacitive/DirectTouch: 298 nits (typical)

with projected capacitive/ThruTouch: 315 nits (typical) (brightness will vary with different materials/thickness that are used to cover the touchscreen)

with SecureTouch: 315 nits (typical)

with surface capacitive: 294 nits (typical)

Response time 17 msec (typical)

Viewing angle (typical, from center) Horizontal (left/right):  $\pm 75^\circ$  or  $150^\circ$  total Vertical

(up/down):  $50/75^\circ$  or  $125^\circ$  total

Contrast ratio 400:1

Input video format Analog (no proprietary video card needed)

Input video signal connector Mini D-Sub 15-Pin VGA type

Input frequency Horizontal: 31.5-60 kHz

Vertical: 56-75 Hz; Power supply Type: Internal power supply

Input (line) voltage: 100-240 VAC, 50-60 Hz

Power consumption 30 W max.

Temperature Operating:  $0^\circ\text{C}$  to  $50^\circ\text{C}$

Storage:  $-30^\circ\text{C}$  to  $60^\circ\text{C}$

Humidity Operating: 20%-80%

Storage: 5%-95%

noncondensing Weight with all options (approx.) Projected Capacitive/DirectTouch actual:

12.1 lb (5.5 kg) Projected Capacitive/DirectTouch shipping: 18.7 lb (8.5 kg) Projected

Capacitive/ThruTouch actual: 11.6 lb (5.3 kg) Projected Capacitive/ThruTouch shipping:

18.2 lb (8.3 kg)